CARBON FREE HOSE C-06 (R CF)



APPLICATION FOR USE IN INDUCTION FURNACE AS CABLE COOLENT & NON-CONDUCTIVE APPLICATION.

LINING WHITE SYNTHETIC RUBBER COMPOUND.

REINFORCEMENT ONE/TWO HIGH TENCITY HEAT RESISTANT SYNTHETIC YARN BRAID/BRAIDS.

COVER GREEN RUBBER COMPOUND WITH ABRASION, WEATHER,HEAT RESISTANCE AND AGEING PROPERTIES.

PRODUCT CODE	NOMINAL BORE		MEAN OUTER COVER DIA-METER	MAXIMUM WORKING PRESSURE		MINIMUM BRUST PRESSURE	
	INCH	M.M	M.M	PSI	BAR	PSI	BAR
C0606	3/8*	10.0*	18.0	290	20.0	1160	80.0
C0608	1/2	12.5	22.5	290	20.0	1160	80.0
C0610	5/8	16.0	26.0	290	20.0	1160	80.0
C0612	3/4	20.0	30.0	290	20.0	1160	80.0
C0616	1	25.0	36.5	290	20.0	1160	80.0
C0620	1-1/4	31.5	435	290	20.0	1160	80.0
C0624	1-1/2	38.0	50.5	250	17.5	1000	70.0
C0632	2	50.0	66.5	250	17.5	1000	70.0

*** WITH ONE HIGH TENCITY HEAT RESISTANT SYNTHETIC YARN BRAID.**